

# MF 9S SERIES // 310-425 HP

ACHIEVE BETTER TOTAL COST OF OWNERSHIP



MASSEY FERGUSON

BORN TO **FARM**

# TIRED OF WATCHING YOUR MONEY EVAPORATE?

In today's ag industry, rising expenses and fuel costs can quickly drain your profits.

## POWERFUL HYDRAULICS AND LINKAGE

- » 90 GPM ECO pump delivers high flow rates for better yields.
- » Right ballast reduces unneeded compaction while providing high levels of traction for heavy draft work.
- » Up to six rear electric spool valves means the MF 9S can adapt to your planting technology and add value to your operation.
- » Up to 26,000 lbs. rear linkage and 11,000 lbs. front linkage capacities take on heavy modern implements with ease.



## POWERFUL EFFICIENCY

- » 8.4-liter AGCO Power™ engine, coupled with the proven Dyna-VT™ transmission, provides maximum power and efficiency for demanding implements.



## ACHIEVE A BETTER COST PER HOUR WITH THE MASSEY FERGUSON® 9S SERIES.

Designed to deliver an industry-leading lower cost of ownership, the MF 9S Series provides up to 15% fuel advantage over other brands.

Better dependability and fewer required services allow farmers to complete fieldwork in the optimum window. And novice operators will require less training with the straightforward yet advanced technology of the MF 9S Series, reducing labor costs and improving efficiency.



**SCAN THE QR CODE**  
for more details about the  
MF 9S Series.



## RECEIVE A LIFETIME OF SUPPORT.

With Massey Ferguson, you can count on personalized, responsive support from our network of dealers throughout the lifetime of your machine.

**ASK YOUR DEALER FOR DETAILS ABOUT AGCO PARTS AND SERVICE.**



## STRAIGHTFORWARD, SMART FARMING

- » MF Care Pro service and extended warranty guarantees optimal performance, reducing servicing and costs.
- » Standard Datatronic™ 5 and optional Fieldstar® 5 touch-screen terminal offers easy operation.
- » MF AutoTurn enables operators to focus on the task at hand, all while increasing efficiency.
- » AutoHeadland ensures that the headland operations are consistent, meaning that no matter your operation speed, the MF 9S reduces operator input.

## SPACIOUS, COMFORTABLE CAB WITH FARMER-FRIENDLY FEATURES

- » Protect-UT™ cab design provides industry-best comfort and visibility.
- » Advanced LED 360° light package features 23 LED lights.
- » MultiPad joystick optimizes control.

## THE RIGHT FEATURES FOR YOUR OPERATION.

The MF 9S series is equipped to Massey Ferguson's highest exclusive specification standards.

|          | COMFORT & SAFETY                                           | EFFICIENCY                                                                                       | CONNECTIVITY                                     |
|----------|------------------------------------------------------------|--------------------------------------------------------------------------------------------------|--------------------------------------------------|
| STANDARD | Quadlink front axle suspension                             | 31 MPH Dyna-VT                                                                                   | Datatronic 5, 9" touch-screen terminal           |
|          | Mechanical active cab suspension                           | Ergonomically designed armrest with MultiPad lever                                               | MF Guide system with Trimble® receiver           |
|          | Protect-U cab                                              | 54 GPM ECO pump                                                                                  | MF Connect telemetry with five-year subscription |
|          | 16 LED working lights & LED beacons                        | Four electrical spool valves with decompression levers and fingertip electrical joystick control | MF TaskDoc® to record and transfer job data      |
|          | Rear camera                                                | MF Care                                                                                          | ISOBUS-compatible terminal                       |
|          | Mirrors with electric de-icing and adjustment              |                                                                                                  |                                                  |
|          | Radio and Bluetooth® technology with integrated microphone |                                                                                                  |                                                  |
| OPTIONS  | Advanced LED 360° light package                            | 90 GPM ECO Dual Circuit Pump                                                                     | MF Autoturn and Automatic Headland               |
|          | Datatronic 5 radio & phone interface                       | 1,000 rpm front PTO                                                                              | MF Wayline Assistant                             |
|          | Large telescopic side mirror with electric adjustment      | 11,000 lbs. Cat 3 front linkage                                                                  | Front ISOBUS socket                              |
|          |                                                            | MF AutoTurn and AutoHeadland                                                                     | MF Section Control and Rate Control              |
|          |                                                            |                                                                                                  | MF TaskDoc Pro                                   |

## TECHNICAL SPECIFICATIONS

|                                               |             | MF 9S.310                                                                                                     | MF 9S.340 | MF 9S.370 | MF 9S.400 | MF 9S.425 |
|-----------------------------------------------|-------------|---------------------------------------------------------------------------------------------------------------|-----------|-----------|-----------|-----------|
| <b>ENGINE TYPE</b>                            |             | AGCO Power                                                                                                    |           |           |           |           |
| No. of cylinders/no. of valves/Capacity       | No./No./L   | 6 / 4 / 8.4                                                                                                   |           |           |           |           |
| Maximum hp                                    | ISO HP (kW) | 310 (228)                                                                                                     | 340 (250) | 370 (272) | 400 (294) | 425 (313) |
| Rated PTO HP                                  | HP          | 235                                                                                                           | 265       | 290       | 320       | 350       |
| Maximum power with EPM                        | HP (kW)     | 340 (250)                                                                                                     | 370 (272) | 400 (294) | 420 (309) | —         |
| <b>DYNA-VT TRANSMISSION</b>                   |             |                                                                                                               |           |           |           |           |
| Number of gears                               | fwd/rev     | Continuously variable transmission                                                                            |           |           |           |           |
| <b>REAR LINKAGE AND HYDRAULICS</b>            |             |                                                                                                               |           |           |           |           |
| Maximum lift capacity, at link end            | lbs.        | 26,000                                                                                                        |           |           |           |           |
| Hydraulic type & max flow                     | l/min       | Closed Center Load Sensing 205 Eco @ 1,650 rpm / 270 l/min @ 1,850 rpm                                        |           |           |           |           |
| Hydraulic type & max flow                     | l/min       | Dual Closed Centre, Load Sensing pump delivers a combined flow of 340 l/min @1,650 rpm / 400 l/min @1,850 rpm |           |           |           |           |
| <b>FRONT LINKAGE AND FRONT POWER TAKE-OFF</b> |             |                                                                                                               |           |           |           |           |
| Maximum lift capacity, at link end            | lbs.        | 11,000                                                                                                        |           |           |           |           |

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.



**SCAN THE  
QR CODE**  
to apply for financing.

